

Benchmark Example No. 4

Design of a Rectangular CS for Bending and Axial Force

VERiFiCATION
DCE-EN4 Design of a Rectangular CS for Bending and Axial Force

VERiFiCATION Manual, Service Pack 2020-14 Build 134

Copyright © 2022 by SOFiSTiK AG, Nuremberg, Germany.

SOFiSTiK AG

HQ Nuremberg
Flataustraße 14
90411 Nürnberg
Germany

T +49 (0)911 39901-0
F +49(0)911 397904

Office Garching
Parkring 2
85748 Garching bei München
Germany

T +49 (0)89 315878-0
F +49 (0)89 315878-23

info@sofistik.com
www.sofistik.com

This manual is protected by copyright laws. No part of it may be translated, copied or reproduced, in any form or by any means, without written permission from SOFiSTiK AG. SOFiSTiK reserves the right to modify or to release new editions of this manual.

The manual and the program have been thoroughly checked for errors. However, SOFiSTiK does not claim that either one is completely error free. Errors and omissions are corrected as soon as they are detected.

The user of the program is solely responsible for the applications. We strongly encourage the user to test the correctness of all calculations at least by random sampling.

Front Cover

Project: Queensferry Crossing | Photo: Bastian Kratzke

Overview	
Design Code Family(s):	DIN
Design Code(s):	DIN EN 1992-1-1
Module(s):	AQB
Input file(s):	rectangular_bending_axial.dat

1 Problem Description

The problem consists of a rectangular section, as shown in Fig. 1. The cross-section is designed for an ultimate moment M_{Ed} and a compressive force N_{Ed} and the required reinforcement is determined.




Figure 1: Problem Description

2 Reference Solution

This example is concerned with the design of sections for ULS, subject to bending with axial force. The content of this problem is covered by the following parts of DIN EN 1992-1-1:2004 [1]:

- Design stress-strain curves for concrete and reinforcement (Section 3.1.7, 3.2.7)
- Basic assumptions for section design (Section 6.1)
- Reinforcement (Section 9.3.1.1, 9.2.1.1)




Figure 2: Stress and Strain Distributions in the Design of Doubly Reinforced Cross-sections

In doubly reinforced rectangular beams, the conditions in the cross-section at the ultimate limit state, are assumed to be as shown in Fig. 2. The design stress-strain diagram for reinforcing steel considered in this example, consists of an horizontal top branch, as presented in Fig. 3 and as defined in DIN EN 1992-1-1:2004 [1] (Section 3.2.7).




Figure 3: Idealised and Design Stress-Strain Diagram for Reinforcing Steel

3 Model and Results

The rectangular cross-section, with properties as defined in Table 1, is to be designed, with respect to DIN EN 1992-1-1:2004 (German National Annex) [1], [2], to carry an ultimate moment of 382 kNm with an axial compressive force of 1785 kN. The calculation steps with a commonly used design method [3] [4] are presented below and the results are given in Table 2. Here, it has to be mentioned that the standard methods employed in order to calculate the reinforcement are approximate, and therefore deviations often occur.

Table 1: Model Properties

Material Properties	Geometric Properties	Loading
C 30/37	$h = 50.0 \text{ cm}$	$M_{Ed} = 382 \text{ kNm}$
B 500A	$d = 45.0 \text{ cm}$	$N_{Ed} = -1785 \text{ kN}$
	$d_1 = d_2 = 5.0 \text{ cm}$	
	$b = 30 \text{ cm}$	

Table 2: Results

	SOF.	Interaction Diagram [3]
$A_{s,tot} [\text{cm}^2/\text{m}]$	35.03	35.19

4 Design Process¹

Design with respect to DIN EN 1992-1-1:2004 (NA) [1] [2]:²

Material:

Concrete: $\gamma_c = 1.50$

Steel: $\gamma_s = 1.15$

$f_{ck} = 30 \text{ MPa}$

$f_{cd} = \alpha_{cc} \cdot f_{ck} / \gamma_c = 0.85 \cdot 30 / 1.5 = 17.0 \text{ MPa}$

$f_{yk} = 500 \text{ MPa}$

$f_{yd} = f_{yk} / \gamma_s = 500 / 1.15 = 434.78 \text{ MPa}$

Design Load:

$N_{Ed} = -1785 \text{ kN}$

$M_{Ed} = 382 \text{ kNm}$

$$\frac{e_d}{h} = \left| \frac{M_{Ed}}{N_{Ed} \cdot h} \right| = \left| \frac{382}{-1785 \cdot 0.50} \right| = 0.428 < 3.5$$

→ Axial force dominant → Design with respect to $\mu - \nu$ interaction diagram is suggested

Design with respect to Interaction diagram for Bending with axial force for rectangular cross-sections:

$$\mu_{Ed} = \frac{M_{Ed}}{b \cdot h^2 \cdot f_{cd}} = \frac{382 \cdot 10^{-3}}{0.30 \cdot 0.50^2 \cdot 17.0} = 0.30$$

$$\nu_{Ed} = \frac{N_{Ed}}{b \cdot h^2 \cdot f_{cd}} = \frac{-1785 \cdot 10^{-3}}{0.30 \cdot 0.50 \cdot 17.0} = -0.70$$

from design chart for $d_1/h = 0.05/0.5 = 0.10$:

$$\omega_{tot} = 0.60$$

$$A_{s,tot} = \omega_{tot} \cdot \frac{b \cdot h}{f_{yd}/f_{cd}} = 35.19 \text{ cm}^2$$

$$A_{s1} = A_{s2} = \frac{A_{s,tot}}{2} = 17.6 \text{ cm}^2$$

(NDP) 2.4.2.4: (1), Tab. 2.1DE: Partial factors for materials

Tab. 3.1: Strength for concrete

3.1.6: (1)P, Eq. (3.15): $\alpha_{cc} = 0.85$ considering long term effects

3.2.2: (3)P: yield strength $f_{yk} = 500 \text{ MPa}$

3.2.7: (2), Fig. 3.8

Tab. 9.6 [3]: $\mu - \nu$ Interaction diagram for concrete C12/15–C50/60 - Rectangular cross-section with double symmetric reinforcement.

¹The tools used in the design process are based on steel stress-strain diagrams, as defined in [1] 3.2.7:(2), Fig. 3.8, which can be seen in Fig. 3.

²The sections mentioned in the margins refer to DIN EN 1992-1-1:2004 (German National Annex) [1], [2], unless otherwise specified.

5 Conclusion

This example shows the calculation of the required reinforcement for a rectangular beam cross-section under bending with axial force. It has been shown that the results are reproduced with excellent accuracy.

6 Literature

- [1] *DIN EN 1992-1-1/NA: Eurocode 2: Design of concrete structures, Part 1-1/NA: General rules and rules for buildings - German version EN 1992-1-1:2005 (D), Nationaler Anhang Deutschland - Stand Februar 2010.* CEN. 2010.
 - [2] F. Fingerloos, J. Hegger, and K. Zilch. *DIN EN 1992-1-1 Bemessung und Konstruktion von Stahlbeton- und Spannbetontragwerken - Teil 1-1: Allgemeine Bemessungsregeln und Regeln für den Hochbau.* BVPI, DBV, ISB, VBI. Ernst & Sohn, Beuth, 2012.
 - [3] K. Holschemacher, T. Müller, and F. Lobisch. *Bemessungshilfsmittel für Betonbauteile nach Eurocode 2 Bauingenieure.* 3rd. Ernst & Sohn, 2012.
 - [4] *Beispiele zur Bemessung nach Eurocode 2 - Band 1: Hochbau.* Ernst & Sohn. Deutschen Beton- und Bautechnik-Verein E.V. 2011.
-