

DIRECT. ALIGNED. TO THE POINT.



Benchmark Example No. 3

## Design of a T-section for Bending

**VERiFiCATION**  
**DCE-EN3 Design of a T-section for Bending**

VERiFiCATION Manual, Service Pack 2024-4 Build 27

Copyright © 2024 by SOFiSTiK AG, Nuremberg, Germany.

**SOFiSTiK AG**

HQ Nuremberg  
Flataustraße 14  
90411 Nürnberg  
Germany

T +49 (0)911 39901-0  
F +49(0)911 397904

Office Garching  
Parkring 2  
85748 Garching bei München  
Germany

T +49 (0)89 315878-0  
F +49 (0)89 315878-23

[info@sofistik.com](mailto:info@sofistik.com)  
[www.sofistik.com](http://www.sofistik.com)

This manual is protected by copyright laws. No part of it may be translated, copied or reproduced, in any form or by any means, without written permission from SOFiSTiK AG. SOFiSTiK reserves the right to modify or to release new editions of this manual.

The manual and the program have been thoroughly checked for errors. However, SOFiSTiK does not claim that either one is completely error free. Errors and omissions are corrected as soon as they are detected.

The user of the program is solely responsible for the applications. We strongly encourage the user to test the correctness of all calculations at least by random sampling.

**Front Cover**

6th Street Viaduct, Los Angeles Photo: Tobias Petschke

## Overview

**Design Code Family(s):** DIN  
**Design Code(s):** DIN EN 1992-1-1  
**Module(s):** AQB  
**Input file(s):** [t-beam\\_bending.dat](#)

## 1 Problem Description

The problem consists of a T-beam section, as shown in Fig. 1. The cross-section is designed for an ultimate moment  $M_{Ed}$  and the required reinforcement is determined.




Figure 1: Problem Description

## 2 Reference Solution

This example is concerned with the design of sections for ULS, subject to pure flexure. The content of this problem is covered by the following parts of DIN EN 1992-1-1:2004 [1]:

- Design stress-strain curves for concrete and reinforcement (Section 3.1.7, 3.2.7)
- Basic assumptions for section design (Section 6.1)
- Reinforcement (Section 9.3.1.1, 9.2.1.1)




Figure 2: Stress and Strain Distributions in the Design of T-beams

In doubly reinforced rectangular beams, the conditions in the cross-section at the ultimate limit state, are assumed to be as shown in Fig. 2. The design stress-strain diagram for reinforcing steel considered

in this example, consists of an inclined top branch, as presented in Fig. 3 and as defined in DIN EN 1992-1-1:2004 [1] (Section 3.2.7).




Figure 3: Idealised and Design Stress-Strain Diagram for Reinforcing Steel

### 3 Model and Results

The T-beam, with properties as defined in Table 1, is to be designed, with respect to DIN EN 1992-1-1:2004 (German National Annex) [1], [2], to carry an ultimate moment of 425 kNm. The calculation steps with different design methods [3] [4] [5] are presented below and the results are given in Table 2. Here, it has to be mentioned that these standard methods employed in order to calculate the reinforcement are approximate, and therefore deviations often occur.

Table 1: Model Properties

Material Properties	Geometric Properties	Loading
C 20/25	$h = 65.0 \text{ cm}$	$M_{Ed} = 425 \text{ kNm}$
B 500A	$d = 60.0 \text{ cm}$	
	$d_1 = 5.0 \text{ cm}$	
	$b = 30 \text{ cm}$	
	$b_{eff} = 258 \text{ cm}$	
	$h_f = 18 \text{ cm}$	

Table 2: Results

	SOF.	$\omega$ —Table [3]	$k_d$ —Table [3]
$A_{s1} [\text{cm}^2/\text{m}]$	15.90	15.74	15.85

## 4 Design Process<sup>1</sup>

### Design with respect to DIN EN 1992-1-1:2004 (NA) [1] [2]:<sup>2</sup>

Material:

Concrete:  $\gamma_c = 1.50$

Steel:  $\gamma_s = 1.15$

$f_{ck} = 20 \text{ MPa}$

$f_{cd} = \alpha_{cc} \cdot f_{ck} / \gamma_c = 0.85 \cdot 20 / 1.5 = 11.33 \text{ MPa}$

$f_{yk} = 500 \text{ MPa}$

$f_{yd} = f_{yk} / \gamma_s = 500 / 1.15 = 434.78 \text{ MPa}$

Design Load:

$N_{Ed} = 0$

$M_{Eds} = M_{Ed} - N_{Ed} \cdot z_{s1} = 425 \text{ kNm}$

(NDP) 2.4.2.4: (1), Tab. 2.1DE: Partial factors for materials

Tab. 3.1: Strength for concrete

3.1.6: (1)P, Eq. (3.15):  $\alpha_{cc} = 0.85$  considering long term effects

3.2.2: (3)P: yield strength  $f_{yk} = 500 \text{ MPa}$

3.2.7: (2), Fig. 3.8

### Design with respect to $\omega$ – (or $\mu_s$ –) Table for T-beams:

$$\mu_{Eds} = \frac{M_{Eds}}{b_{eff} \cdot d^2 \cdot f_{cd}} = \frac{425 \cdot 10^{-3}}{2.58 \cdot 0.60^2 \cdot 11.33} = 0.040$$

Tab. 9.4 [3]:  $\omega$ –Table for up to C50/60 - T-beam

Referring to the design table for T-beams for:

$\mu_{Eds} = 0.040$  and

$$\frac{h_f}{d} = \frac{0.18}{0.60} = 0.30; \quad \frac{b_{eff}}{b_w} = \frac{2.58}{0.30} = 8.6$$

$\rightarrow \omega_1 = 0.039$

$$A_{s1} = \frac{1}{f_{yd}} \cdot (\omega_1 \cdot b_{eff} \cdot d \cdot f_{cd} + N_{Ed}) = 15.74 \text{ cm}^2$$

### Design with respect to $k_d$ – Design Table for T-beams:

Alternatively, the  $k_d$ –Tables can be applied, demonstrated that the neutral line lies inside the flange.

$$k_d = \frac{d}{\sqrt{M_{Eds}/b}} = \frac{60}{\sqrt{425/2.58}} = 4.67$$

Tab. 9.3 [3]:  $k_d$ –Table for up to C50/60 - Rectangular section without compression reinforcement

Referring to the table for  $k_d = 4.67$  and after interpolation

$\rightarrow k_s = 2.351; \quad \xi = 0.060; \quad \kappa_s = 0.952$

$x = \xi \cdot d = 0.060 \cdot 60 = 3.6 \text{ cm}; \quad h_f = 18 \text{ cm}$

$$A_{s1} = \left( k_s \cdot \frac{M_{Eds}}{d} + \frac{N_{Ed}}{\sigma_{s1d}} \right) \cdot \kappa_s = 15.85 \text{ cm}^2$$

$k_d$ –Table is applicable since the neutral line lies inside the flange

<sup>1</sup>The tools used in the design process are based on steel stress-strain diagrams, as defined in [1] 3.2.7:(2), Fig. 3.8, which can be seen in Fig. 3.

<sup>2</sup>The sections mentioned in the margins refer to DIN EN 1992-1-1:2004 (German National Annex) [1], [2], unless otherwise specified.



## 5 Conclusion

This example shows the calculation of the required reinforcement for a T-beam under bending. Two different reference solutions are employed in order to compare the SOFiSTiK results to. It has been shown that the results are reproduced with excellent accuracy.

## 6 Literature

- [1] *DIN EN 1992-1-1/NA: Eurocode 2: Design of concrete structures, Part 1-1/NA: General rules and rules for buildings - German version EN 1992-1-1:2005 (D), Nationaler Anhang Deutschland - Stand Februar 2010.* CEN. 2010.
  - [2] F. Fingerloos, J. Hegger, and K. Zilch. *DIN EN 1992-1-1 Bemessung und Konstruktion von Stahlbeton- und Spannbetontragwerken - Teil 1-1: Allgemeine Bemessungsregeln und Regeln für den Hochbau.* BVPI, DBV, ISB, VBI. Ernst & Sohn, Beuth, 2012.
  - [3] K. Holschemacher, T. Müller, and F. Lobisch. *Bemessungshilfsmittel für Betonbauteile nach Eurocode 2 Bauingenieure.* 3rd. Ernst & Sohn, 2012.
  - [4] *Beispiele zur Bemessung nach Eurocode 2 - Band 1: Hochbau.* Ernst & Sohn. Deutschen Beton- und Bautechnik-Verein E.V. 2011.
  - [5] R. S. Narayanan and A. W. Beeby. *Designers' Guide to EN 1992-1-1 and EN 1992-1-2 - Eurocode 2: Design of Concrete Structures.* Thomas Telford, 2005.
-